



- 1 Flexible high quality elastomeric insert**
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Multi directional movement**
- 3 Quick and easy installation**
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- Flexible adaptation to site conditions**
Available with adjustable installation height
- 4 MultiHole mounting bracket**
for secure fixing

Expansion joint cover	Joint width	Total movement	Visible width	Total width	Joint height	Load bearing capacity*	Load bearing capacity*
	b _{f max} [mm]	Δb _f [mm]	b _s [mm]	b _t [mm]	h [mm]	[kN]	[kN]
FV 41/15	35	14 (±7)	41	114	15	30	30
FV 41/20	35	14 (±7)	41	114	20	30	30
FV 41/25	35	14 (±7)	41	114	25	30	30
FV 41/35	35	14 (±7)	41	131	35	30	30
FV 41/50	35	14 (±7)	41	131	50	30	30
FV 41/4055	35	14 (±7)	41	114	40, 45, 50, 55	30	30
FV 41/6075	35	14 (±7)	41	114	60, 65, 70, 75	30	30
FV 41/7590	35	14 (±7)	41	114	75, 80, 85, 90	30	30
FV 41/90105	35	14 (±7)	41	114	90, 95, 100, 105	30	30

* no continuous use

All info on load capacities apply to doweled, not to floating installation.

For installation in asphalt, please ask for our technical advice.

Production length: 4 m

Standard colours: black, grey, beige

Wall connections: E1, E3, E4

