



- 1 Flexible high quality elastomeric insert**
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Smooth visible surface for easy cleaning**
Antibacterial and physiologically safe
- 3 Quick and easy installation**
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- 4 MultiHole mounting bracket**
for secure fixing
- 5 Flexible adaptation to site conditions**
Available with adjustable installation height

| Expansion joint cover | Joint width | Total movement | Visible width | Total width | Joint height | Load bearing capacity*  [kN] | Load bearing capacity*  [kN] |
|-----------------------|------------------------|-------------------|---------------|-------------|------------------|---|---|
| | $b_f \text{ max}$ [mm] | Δb_f [mm] | b_s [mm] | b_t [mm] | h [mm] | | |
| FG 35/15 | 30 | 6 (± 3) | 35 | 108 | 15 | 30 | 30 |
| FG 35/20 | 30 | 6 (± 3) | 35 | 108 | 20 | 30 | 30 |
| FG 35/25 | 30 | 6 (± 3) | 35 | 108 | 25 | 30 | 30 |
| FG 35/35 | 30 | 6 (± 3) | 35 | 125 | 35 | 30 | 30 |
| FG 35/50 | 30 | 6 (± 3) | 35 | 125 | 50 | 30 | 30 |
| FG 35/4055 | 30 | 6 (± 3) | 35 | 108 | 40, 45, 50, 55 | 30 | 30 |
| FG 35/6075 | 30 | 6 (± 3) | 35 | 108 | 60, 65, 70, 75 | 30 | 30 |
| FG 35/7590 | 30 | 6 (± 3) | 35 | 108 | 75, 80, 85, 90 | 30 | 30 |
| FG 35/90105 | 30 | 6 (± 3) | 35 | 108 | 90, 95, 100, 105 | 30 | 30 |

* no continuous use

All info on load capacities apply to doweled, not to floating installation.
For installation in asphalt, please ask for our technical advice.

Production length: 4 m

Standard colours: black, grey, beige, brown

Wall connections: E1, E3, E4

